



BRIGHT Square Flood

FEATURES:

Housing	Die-casting aluminium
Housing Color	Black
Finishes	Anodized aluminium
Installation Holder	Stainless steel
Protection	IP66
Working Temperature	-25°C to +50°C
Beam Angle	20° / 40° / 60°
CCT	3000 K / RGB / RGBW

- Nicely outlooking extra slim design.
- Glueless construction waterproof design
- Trimless design
- The light transmittance of tempered glass is more than 92%
- Rotary support with locking system

IP
66

- Offices
- Classrooms
- Auditoriums
- Hospitals
- Sports Halls
- Industries

Product Code	Size (mm) L x B x H
BFL - 0612	60 x 60 x 70
BFL - 1224	100 x 100 x 105
BFL - 8010	200 x 200 x 198
BFL - 12050	200 x 300 x 216
BFL - 16020	300 x 300 x 236
BFL - 22030	300 x 400 x 250
BFL - 32038	400 x 400 x 295

BRIGHT Square Flood

Specifications

Input Voltage	: 24 V DC / 240V AC
Frequency	: 50/60 Hz
Power Factor @230 VAC	: > 0.9
Colour Temperatures	: 3000 K / RGBW / RGB
Colour Rendering Index	: > 80
Lumen Efficacy	: 100 Lumens per Watt
Ingress Protection	: IP66
Life Span	: 50,000 Hours
Safety Standard	: IEC 60598
EMC/ EMI Standard	: IEC61547 / EN55015
Harmonics	: IEC 61000-3-2

Product Code	Input Power	System Lumens	Energy Savings
BFL - 0612	6-12 Watts	600-1200	50%
BFL - 1224	12-24 Watts	1200-2400	50%
BFL - 8010	80-100 Watts	8000-10000	50%
BFL - 12050	120-150 Watts	12000-15000	50%
BFL - 16020	160-200 Watts	16000-20000	50%
BFL - 22030	220-300 Watts	22000-30000	50%
BFL - 32038	320-380 Watts	32000-38000	50%

Specifications subject to change

Mechanical Diagram

