



FILLO

FEATURES:

Housing	Die-casting aluminium
Housing Color	Black
Finishes	Anodized aluminium
Installation Holder	Stainless steel
Protection	IP66
Working Temperature	-25°C to +45°C
Beam Angle	270° / 540°
Smooth and Quiet linear zoom	4° to 45°
Flicker free operation for broadcast TV and FILM	

Today more and more moving heads are being exposed to wet, humid and extreme conditions. With numerous multi-environmental application requirements, Color Imagination recently launched an IP65 rated hybrid LED moving head with CMY+CTO system which integrates BEAM, SPOT and WASH in one fixture, featuring linear zoom ranging from 4° to 45°.

The SPOT features a new high intensity and efficiency cool white 550W LED engine (8500K) delivering a total of 22200 lumens for ultra high light output through a set of high resolution and precise optics that helps to provide extremely clear and even spot coverage.

IP
65



Specifications

Input Voltage	: AC100-240V
Frequency	: 50/60 Hz
Power Factor @230 VAC	: > 0.9
Colour Temperatures	: 8500 K
Colour Rendering Index	: > 70
Lumen Efficacy	: 40.36 Lumens per Watt
Ingress Protection	: IP66
Life Span	: 30,000 Hours
Safety Standard	: IEC 60598
EMC/ EMI Standard	: IEC61547 / EN55015
Harmonics	: IEC 61000-3-2

Product Code	Size (mm) D x W x H
FTL - 150	325 x 444 x 671
FTL - 550	325 x 444 x 671

Product Code	Input Power	System Lumens
FTL - 150	150 Watts	6050
FTL - 550	550 Watts	22200