

FOCUS Round Flood

Specifications

Input Voltage	: 24 V DC / 240V AC
Frequency	: 50/60 Hz
Power Factor @230 VAC	: > 0.9
Colour Temperatures	: 3000 K / RGBW / RGB
Colour Rendering Index	: > 80
Lumen Efficacy	: 100 Lumens per Watt
Ingress Protection	: IP66
Life Span	: 50,000 Hours
Safety Standard	: IEC 60598
EMC/ EMI Standard	: IEC61547 / EN55015
Harmonics	: IEC 61000-3-2



FOCUS Round Flood

Applications

- Offices
- Classrooms
- Auditoriums
- Hospitals
- Sports Halls
- Industries

FEATURES:

Housing	Die-casting aluminium
Housing Color	Black
Finishes	Anodized aluminium
Installation Holder	Stainless steel
Protection	IP66
Working Temperature	-25°C to +50°C
Beam Angle	20° / 40° / 60°
CCT	3000 K / RGB / RGBW



- Nicely outlooking extra slim design.
- Glueless construction waterproof design
- Trimless design
- The light transmittance of tempered glass is more than 92%
- Rotary support with locking system

Product Code	Size (mm) Ø x H
FFL - 340	40 x 55
FFL - 69	60 x 132
FFL - 612	80 x 88
FFL - 1825	120 x 234
FFL - 3060	170 x 168
FFL - 4855	160 x 304
FFL - 80100	240 x 212
FFL - 10015	280 x 242
FFL - 16025	40 x 55

Product Code	Input Power	System Lumens	Energy Savings
FFL - 340	03 Watts	300	50%
FFL - 69	6-9 Watts	600-900	50%
FFL - 612	6-12 Watts	600-1200	50%
FFL - 1825	18-25 Watts	1800-2500	50%
FFL - 3060	30-60 Watts	3000-6000	50%
FFL - 4855	48-55 Watts	4800-5500	50%
FFL - 80100	80-100 Watts	8000-10000	50%
FFL - 10015	100-150 Watts	10000-15000	50%
FFL - 16025	160-250 Watts	16000-25000	50%

Specifications subject to change

Mechanical Diagram

