



OPTIMA Linear

FEATURES:

Housing	Die-casting aluminium
Housing Color	Black
Finishes	Anodized aluminium
Installation Holder	Stainless steel
Protection	IP66
Working Temperature	-25°C to +50°C
Beam Angle	20° / 40° / 60°
CCT	3000 K / RGB / RGBW

- Nicely outlooking extra slim design.
- Glueless construction waterproof design
- Trimless design
- The light transmittance of tempered glass is more than 92%
- Rotary support with locking system

IP
66

Applications

Offices
Classrooms
Auditoriums
Hospitals
Sports Halls
Industries

Product Code	Size (mm) (LxH)
OLL - 1810	1000 x 20
OLL - 2410	1000 x 25
OLL - 3610	1000 x 25

OPTIMA Linear

Specifications

Input Voltage	: 24 V DC / 240V AC
Frequency	: 50/60 Hz
Power Factor @230 VAC	: > 0.9
Colour Temperatures	: 3000 K / RGBW / RGB
Colour Rendering Index	: > 80
Lumen Efficacy	: 100 Lumens per Watt
Ingress Protection	: IP66
Life Span	: 50,000 Hours
Safety Standard	: IEC 60598
EMC/ EMI Standard	: IEC61547 / EN55015
Harmonics	: IEC 61000-3-2

Product Code	Input Power	System Lumens	Energy Savings
OLL - 1810	18 Watts	1800	50%
OLL - 2410	24 Watts	2400	50%
OLL - 3610	36 Watts	3600	50%

Specifications subject to change



Mechanical Diagram

