



## PAVER Ground Uplight



### Applications


- Concrete Paving
- Driveways
- Pathways

### Features

- Mounting : Ground
- High corrosion resistant die cast aluminium housing and polypropylene housing for recessing
- Polyester painting with phosphocromating pre finish
- Stainless steel AISI 304 ring
- Clear tempered glass for static load load-bearing capacity of up to 5000kg.
- Best in class power LEDs from reputed international companies
- Inbuilt power LED driver
- High efficiency lens (available in 10° / 30° / 45° Beam angle) for excellent
- Body Colour : Stainless steel

### Mechanical Features

Product Code	Product Code	Size (mm) Ø x H	Static Weight Resistance	Weight
XG 04 14	Paver Micro	Ø120 x H100	1000 Kg.	0.7 Kg.
XG 04 13	Paver Mini	Ø135 x H116	5000 Kg.	1.25 Kg.
XG 04 12	Paver Medium	Ø190 x H110	5000 Kg.	2.1 Kg.
XG 04 11	Paver Maxi	Ø1265 x H110	5000 Kg.	5.0 Kg.



## PAVER Ground Uplight


### Specifications

Input Voltage	: 190 V - 250 V AC
Frequency	: 50/60 Hz
Power Factor @230 VAC	: > 0.9
Colour Temperatures	: 3000 K / 4000 K / 6000 K
Colour Rendering Index	: > 70
Operating Temperature	: -20° C to 50° C
Ingress Protection	: IP67
Impact Protection	: IK09
Life Span	: 50,000 Hours
Safety Standard	: EN 60598
EMC/ EMI Standard	: EN61547 / EN55015
Harmonics	: EN61000-3-2 and 61000-3-3

Product Code	Product Code	Input Power	System Lumens
XG 04 14	Paver Micro	1 Watt	70
XG 04 13	Paver Mini	3 Watts	120
XG 04 12	Paver Medium	8 Watts	750
XG 04 11	Paver Maxi	12 Watts	1100

Specifications subject to change

## Urban Lighting



XG 04 11



XG 04 13



XG 04 13

### Photometric Data

\*Polar Candela Distribution

