



ZODIAC Lights

IP
65

Features

- Mounting: Recessed / Surface / Suspended
- Housing: Pressure die cast aluminium
- Best in class power LEDs
- Standard Body Colour : White. Other options available.

Mechanical Features

Product Code	Size (mm)
ZL - 030	400 x 65
ZL - 040	600 x 65
ZL - 050	800 x 65
ZL - 060	1000 x 65
ZL - 070	1200 x 65

Product Code	Input Power	System Lumens	Energy Saving
ZL - 030	30 Watts	3000	65 %
ZL - 040	40 Watts	4000	65 %
ZL - 050	50 Watts	5000	65 %
ZL - 060	60 Watts	6000	65 %
ZL - 070	70 Watts	7000	65 %



Specifications

Input Voltage	: 100 V - 285 V AC
Frequency	: 50/60 Hz
Power Factor @230 VAC	: > 0.9
Colour Temperatures	: 3000 K / 4000 K / 6000K
Colour Rendering Index	: > 80
Lumen Efficacy	: Up to 100 Lumen / W
Ingress Protection	: IP55
Life Span	: 75,000 Hours
Safety Standard	: IEC 60598
EMC/ EMI Standard	: IEC61547 / EN55015
Harmonics	: IEC 61000-3-2

Specifications subject to change