



# FUTURA MINI

## For Street Lighting



Goldwyn's new FUTURA MINI LED street light made of PDC aluminium powder coating Housing, High impact resistant clear polycarbonate cover with matrix of power LED's offers life long characteristics with energy reduction compared to conventional technologies. The system along with the best in class Strada Optic lenses and a variety of wattage options delivers uniform wide distribution and energy efficient illumination.

### Features

- Mounting : Pole.
- High grade pressure Die casted aluminium housing.
- High Impact resistant clear poly carbonate cover.
- High corrosion resistant powder coating for excellent durability.
- Best in class power LED's from reputed international companies.
- Inbuilt electronic driver with upto 4 KV surge protection.
- High efficiency PMMA lens for excellent light distribution.
- Body Colours : Black / Grey

### SPECIFICATIONS

Input Voltage	100 V – 265 V AC, 12 V / 24 V DC
Frequency	50 / 60 Hz
Power Factor @230 VAC	> 0.9
Colour Temperatures	3000 K / 4000 K / 6000 K
Colour Rendering Index	> 70
Lumens Efficacy	> 90 Lumens per Watt
Operating Temperature	-20 C to 50 C
Ingress Protection	IP65
Impact Protection	IK10
Life Span	50,000 Hours
Safety Standard	EN 60598
EMC / EMI Standard	EN61547 / EN55015
Harmonics	EN61000-3-2 and 61000-3-3

